

TORNADO



ELITE AND CLASSIC HOME SOCCER PLAYFIELD REPLACEMENT

Tools Required:

- ELECTRIC DRILL WITH 9/64" BIT
- PHILLIPS SCREWDRIVER
- RIGHT ANGLE PHILLIPS SCREWDRIVER
- ALL-PURPOSE CLEANER (*Fantastik, Formula 409, Windex or equivalent*)
- CLEAN CLOTH
- SMALL HAMMER
- SMALL PRY BAR OR PUTTY KNIFE

1. Have two people carefully turn the cabinet upside down on a soft surface such as carpeting. Be **very careful** not to scratch the table in the process.
2. Remove the ball return system by removing the Phillips head screws and any additional fasteners, or adhesives. This is where you may need the hammer, putty knife or pry bar. Exercise care as this return system was not really designed for easy removal or replacement. Take care to note its orientation for re-installation on the new playfield.

This step is fairly complex and will take time and care to do properly. The words "remove the roof of your home and note its installation" are simple to write, but the actual process is a whole lot more complicated. Know for sure if you are comfortable doing this before proceeding, because it's not something you can really blow off midway through. Once you start, you're committed!

3. Using the right-angle Phillips screwdriver, remove the four screws in each goal end.
4. Remove the playfield, install the new playfield, and place the original playfield atop the new playfield to use as a template to drill mounting holes using the 9/64" bit.
5. Reinstall the goal end screws and ball return system removed in steps 3 and 2.
6. Have two people carefully turn the cabinet top half right side up and re-install on cabinet bottom half.
7. Thoroughly clean the playfield and install the playfield trim.

VISIT WWW.VALLEY-DYNAMOPARTS.COM FOR WARRANTY REGISTRATION
AND REPLACEMENT PARTS ORDERS. ENJOY YOUR TORNADO TABLE.

